

LTE Radios




IP ADVANCED RADIO SYSTEM



Instant Wide Area Coverage Over an LTE (4G) and 3G Network

LTE radio provides instantaneous, wide area communication using an LTE (4G) and 3G network*. LTE radio doesn't require its own repeaters or IP network, therefore reducing the cost of building, and maintaining a wide area radio network.

* Service availability depends on the country. Network coverage provided by a custom SIM card.



One-to-Many Communication

Unlike mobile phones, the IP503H/IP501M users can immediately start talking to all the radios in the same talkgroup, with just a push of the transmit (PTT) button.



Full-Duplex Communication

Our LTE Radios use full-duplex conversation, which allows users to talk and receive at the same time. This allows smooth, telephone like conversations.



Priority Interrupt Calling

The LTE radios provide group calling with three or more people. In case of an emergency, you can break into an on-going call to transmit an important message.



Multiple User Communication

Multiple users in the call groups can initiate calls in a instant, removing the need to wait for available channels to communicate.



Compact and Durable LTE Handheld



900 mW powerful, high quality audio with wideband, near lossless G.726 vocoder

IP67 waterproof and dust-tight (1 m depth water for 30 minutes)

Emergency Call, Lone Worker and Man Down functions

Voice Record/Playback functions

Vibration Alert function notifies of incoming calls

Built-in Bluetooth® and GPS

And More

- Optional BC-218 charger cradle and HM-215 speakermicrophone, the Bluetooth® function enables you to wirelessly use the speaker-microphone connected to the charger
- Text message reception and preprogrammed message transmission Up to 500 memory address book (including Group, Individual, Talk Group and telephone*) Full duplex communication Full dot-matrix display

* VE-PG4 required.

Supplied accessories

• BP-272 Li-ion battery pack • MB-135 belt clip • Hand strap • Antenna

LTE Mobile Radio

Slim and Feature Packed LTE Mobile



LTE RADIO

IP501M

Built-in Bluetooth® and GPS

Ethernet port for data communication*

* The optional VE-PG4 is required.



Text message reception and preprogrammed message transmission

Emergency call and Lone Worker functions

Noise Cancelling function (TX only)

And More

Meets IP54 and MIL-STD-810G standards • D-SUB 25-PIN connector with optional OPC-2407 cable for interfacing with other devices, various controls and data communication • Up to 500 memory address book (including Group, Individual, Talk Group and telephone*) • Full duplex communication • Full dot-matrix display • Both 12 and 24 volt compatible
 * VE-PG4 required.

Supplied accessories

- HM-241 speaker-microphone LTE antenna (2 pcs) GPS antenna
- DC power cable Mounting bracket kit Microphone hanger

Just Put the IP503H in the Slot and Start a Conference Call



SPEAKERPHONE UNIT VE-SP1

- Portable operation with LR6 (AA) × 8 cells
- Built-in loudspeaker and high sensitivity external microphone
- Charges the radio when using the AC adapter

Supplied accessories

• OPC-2397 connection cable • BC-242 AC adapter • SM-1 external microphone

* The LTE radio is not supplied.

OPTIONS (For Handheld Radio)



BC-218 +MBA-7+MBF-1 With Bluetooth®







CS-IP501H Programming software OPC-478UC Programming cable













OPC-2359 Required when using the HS-102



- CP-22 With DC-DC converter, 12-24 V DC CP-23L 12 V DC
- *1 AC adapter may be supplied as standard, depending on the version.
- *2 BC-123SA for USA plug, SE for Europe plug, SV for Australia plug.



HM-230HB

- Saves space and fully controls the IP501M
- Direct message and calling ID input
- Four function assignable buttons (Emergency/P1/P2/P3)

OPTIONS (For Mobile Radio)













PROGRAMMING SOFTWARE
 CS-IP501M Programming software







iOS™/Android™ Application to Communicate with LTE Radios





iOS™/Android™ APPLICATION

IP500APP

Use your smartphone^{*1} to talk and listen to the LTE radios. The IP500APP application^{*2} lets you join the radio fleet as if you are using the real radio.

Main features


- Full-Duplex communication Short text message
- Voice Recording/Playback function Address book
- TX/RX history
- *1 IP500APP for iOS™: iOS™ version 12 or later IP500APP for Android™: Android™ version 8.0 or later
- *2 IP500APP service may not be available and will be ready in the future.

Radio Gateway — Link LTE Radios to Private Mobile Radios, WLAN Radios, IP Phone Systems and More

The VE-PG4 is a versatile RoIP (Radio over IP network) gateway unit, which seamlessly interconnects LTE radios, private mobile radios, WLAN radios, IP phone systems, SATELLITE PTT radios and external devices. The built-in LTE module* provides virtually nationwide communication coverage.

* Service availability depends on the country. Network coverage provided by a custom SIM card.






SPECIFICATIONS


		IP503H (Handheld radio)	IP501M (Mobile radio)	
Network	USA	-	LTE (4G) bands: B2, B4, B12 W-CDMA (3G) bands: B2, B5	
	EXP	LTE (4G) bands: B1, B3, B7, B8, B20 W-CDMA (3G) bands: B1, B8	LTE (4G) bands: B1, B3, B7, B8, B20 W-CDMA (3G) bands: B1, B8	
	AUS	LTE (4G) bands: B1, B3, B5, B7, B8, B28 W-CDMA (3G) bands: B1, B5	LTE (4G) bands: B1, B3, B5, B7, B8, B28 W-CDMA (3G) bands: B1, B5	
Dimensions (W x H x D; projections not included)		59 x 95 x 32 mm; 2.3 x 3.7 x 1.3 in (Approximate, with BP-272)	125 × 29 × 156 mm; 4.9 × 1.1 × 6.1 in (Approximate)	
Weight (approximate)		240 g; 8.5 oz (with BP-272 and antenna) 840 g, 1.9 lb (Main unit)		
Voice Codec		G.726 (32 kbps)	G.726 (32 kbps)	
AF output power	Internal SP	More than 900 mW (8 Ω at 10% distortion)	-	
	External SP	More than 200 mW (8 Ω at 10% distortion)	More than 4 W (4 Ω at 10% distortion)	
Operating time		17 hours (with BP-272) (TX : RX : Standby= 5 : 5 : 90)	-	
Bluetooth®		Ver 2.1 +EDR	Ver 2.1 +EDR	
GPS		Built-in	Built-in (External GPS antenna supplied)	
LAN		-	RJ-45 type × 1 (AUTO MDI/MDI-X) 100BASE-TX/10BASE-T	


		VE-PG4
	USA	LTE (4G) bands: B2, B4, B12 W-CDMA (3G) bands: B2, B5
Network	EXP	LTE (4G) bands: B1, B3, B7, B8, B20 W-CDMA (3G) bands: B1, B8
	AUS	LTE (4G) bands: B1, B3, B5, B7, B8, B28 W-CDMA (3G) bands: B1, B5
Power supply	,	12 V DC ±10%, 4 A maximum 100-240 V AC (with the supplied AC adapter)
Dimensions (W x	H x D; projections not included)	213 × 36.8 × 270 mm, 8.4 × 1.4 × 10.6 in (Approximate)
Weight		1.8 kg, 4 lb (Main unit, approximate)
WAN/LAN		RJ-45 type x 1 (Auto MDI/MDI-X) 10BASE-T/100BASE-TX/1000BASE-T *WAN/LAN port selectable.
LAN		RJ-45 type x 1 (Auto MDI/MDI-X) 10BASE-T/100BASE-TX/1000BASE-T
Internet proto	col	IPv4
Call Control F	Protocol	SIP
Codec		G.711 µ-law, AMBE+2™
	LTE Radios	IP501H, IP503H, IP501M
	WLAN Radio	IP100H
	Satellite PTT	IC-SAT100
Compatible	VHF/UHF Repeaters	IC-FR5000, IC-FR5100, IC-FR6000, IC-FR6100
models	VHF/UHF Radios	IC-F5061D, IC-F5062D, IC-F5063D, IC-F6061D, IC-F6062D, IC-F6063D
	VHF Marine Radios	IC-M605, IC-M605EURO
	VHF Air Band Radios	IC-A120, IC-A120E

DIMENSIONS



REAR PANEL VIEW





CASE STUDIES

Japan Airlines

Simultaneous communication system leads to quick and high quality service at low cost.





Osaka Metro

Osaka Metro has introduced the Icom LTE radios in all 133 stations.





Please ask your Icom distributor in your country about the planned launch date of the service or other requirements. This product requires the system construction working in collaboration with a mobile network operator. Icom, Icom Inc. and Icom Iogo are registered trademarks of Icom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand and/or other countries. IDAS and COMMANDMIC are trademarks of Icom Incorporated. The Bluetooth® word mark and Iogos are registered trademark owned by Bluetooth SIG, Inc. and any use of such marks by Icom Inc. is under license. AMBE+2 is a trademark and property of Digital Voice Systems Inc. Android is a trademark or registered trademark of Google LLC. IOS is a trademark or registered trademark of Cisco in the U.S. and other countries and is used under license. All other trademarks are the properties of their respective holders.

ICOM INC. 1-1-32, Kamiminami, Hirano-Ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013

www.icom.co.jp/world

Count on us!

Icom America Inc. www.icomamerica.com

Icom Canada www.icomcanada.com

Icom Brazil

E-mail: sales@icombrazil.com

Icom (Europe) GmbH www.icomeurope.com

Icom Spain S.L. www.icomspain.com

Icom (UK) Ltd. www.icomuk.co.uk

Icom France s.a.s. www.icom-france.com

Icom (Australia) Pty. Ltd. www.icom.net.au

Shanghai Icom Ltd. www.bjicom.com

Your local distributor/dealer: